

Palniki gazowe

Characteristics

1. Powered by natural gas or liquefied gas
2. Single-stage burner (on / off)
3. Gas/air mixer in the combustion tube
4. Possibility of obtaining optimal combustion conditions thanks to air regulation and the head
5. No need to remove the entire flange for maintenance, the burner can be easily disassembled.
6. Manual flow adjustment
7. One flange and one insulating pad for connection to the exchanger
8. Air inlet manually adjustable with a deflector
9. Single-phase motor powering the pump and blower
10. Flame detector - ionization electrode
11. Degree of protection IP 40
12. Quiet air intake
13. Plastic housing

[płynový hořák. BTG 12 L300 \(35 - 115kW\) bez rozchodu](#)

Kod: 4401

ceník

5116.61 PLN

{netto}

6293.43 PLN

{brutto}

Palnik gaz. BTG 12 L300 (Ścieżka 1/2") Kompletny

Kod: 5599

ceník

7076.16 PLN

{netto}

8703.68 PLN

{brutto}

Palnik gazowy Riello BS2TXL + MBD405 z długą lufą

Kod: 9053

ceník

7862.40 PLN

{netto}

9670.75 PLN

{brutto}

Produkt byl přidán do košíku!

[Pokračovat v nákupu](#) [Přejít do košíku](#)